

Gigabit DC to DC Converter

Features

- Input Voltage 12VDC or 24VDC or 48VDC
- IEEE 802.3af Compliant or Passive PoE Output
- Dual Inputs for Connecting 2 Power Sources
- Integrated 10/100/1000MB PoE Inserter
- High Power up to 24W
- Low Self Consumption Power
- Short Circuit, Over Current and Reverse/Over Voltage Protect
- High Temperature Operation
- Compact Size – Maximize Available Space



TP-DCDC-1248GD
17W 802.3af

Applications

- 12V / 24V / 48V Battery Systems, Vehicle Applications
- Wireless Access Points and Client Devices
- IP Phone and Security Camera Systems
- PoE Lighting Applications

Description

The TP-DCDC Gigabit Series of DC to DC converters offered by Tycon Power® are a low cost and high efficiency solution for those requiring IEEE802.3af or Passive Power over Ethernet from a 12VDC or 24VDC or 48VDC voltage source like a battery system or vehicle. They have an integrated POE injector to apply the power and data output to the CAT5 Ethernet cable. The output voltage is regulated and protected. They have two isolated inputs for connecting 2 power sources, like a primary and backup power source. A metal enclosure model is available for industrial applications.

They accept gigabit data-in to a shielded RJ45 Jack and provide gigabit data-out and PoE power on the shielded RJ45 output jack. They work by supplying power on Ethernet pins 4,5(V+) and 7,8(V-). They have various protections for surge, short circuit and overload. The units have power outputs up to 24W.

Device Pinouts

RJ-45 Input (Data Only)			RJ-45 Output (Data & Power)	
Pin	Symbol	Description	Symbol	Description
1	BI_DA+	Data Pair A+	BI_DA+	Data Pair A+
2	BI_DA-	Data Pair A-	BI_DA-	Data Pair A-
3	BI_DB+	Data Pair B+	BI_DB+	Data Pair B+
4	BI_DC+	Data Pair C+	+Vdc + BI_DC+	power(+)+Data Pair C+
5	BI_DC-	Data Pair C-	+Vdc + BI_DC-	power(+)+Data Pair C-
6	BI_DB-	Data Pair B-	BI_DB-	Data Pair B-
7	BI_DD+	Data Pair D+	-Vdc + BI_DD+	power(-)+Data Pair D+

8	BI_DD-	Data Pair D-	-Vdc + BI_DD-	power(-)+Data Pair D-
---	--------	--------------	---------------	-----------------------

Specifications

	TP-DCDC-1224G	TP-DCDC-1248G	TP-DCDC-1248GD	TP-DCDC-1248GD-M	TP-DCDC-4824G	TP-DCDC-4848G
DC Input Voltage	9VDC – 36VDC	9VDC – 36VDC	9VDC – 36VDC	9VDC – 36VDC	36VDC-72VDC	36VDC-72VDC
DC Input Current	2.86A @ 9V 0.67A @ 36V	1.85A @ 12V 0.9A @ 24V	1.85A @ 12V 0.9A @ 24V	1.85A @ 12V 0.9A @ 24V	0.84A @ 36V 0.43A @ 72V	0.84A @ 36V 0.43A @ 72V
DC Input Connector	Removeable Screw Type Compression Wire Terminal (12 AWG Max)					
DC Output Voltage	24V (Passive)	48V (Passive)	48V (802.3af)	48V (802.3af)	24V (Passive)	48V (Passive)
Data in & Data/POE Output Connector	RJ45 (Shielded)					
Output Current (max)	0.8A	0.42A	0.35A	0.35A	0.84	0.5A
Output Power (max)	20W	20W	17W	17W	20W	24W
Self Consumption Power	1W					
Efficiency (min)	75%					
Line Regulation	1%					
Load Regulation	5%					
Ripple	1%					
Noise	1%					
EMC Standards	FCC Class B EN55022 Class B					
Safety Standards	CSA 22.2 & TUV EN60950					
Operating Temp	-30 to +60°C (-22 to +140°F)					
Operating Humidity	5% - 90%					
Storage Temp	-40 to +80°C (-40 to +176°F)					
MTBF (Mean Time Between Failure)	166,000 Hours					111,863 Hrs
Dimensions (LxWxH)	85 x 76 x 36mm (3.4 x 3 x 1.4")					
Weight	134g (4.7oz)					
Warranty	3 Years					



TP-DCDC-1248GD-M
(Metal Enclosure)

DC Input

FG		Frame Ground Do Not connect to VIN-
VIN-		DC (-) Voltage In
VIN+		DC (+) Voltage In Isolated Input #1
VIN+		DC (+) Voltage In Isolated Input #2

System Ordering:

TP-DCDC-1224G

9-36VDC IN, 24VDC Passive PoE OUT, 20W DCDC Converter with Gige PoE Inserter

TP-DCDC-1248G

9-36VDC IN, 48VDC Passive PoE OUT, 20W DCDC Converter with Gige PoE Inserter

TP-DCDC-1248GD

9-36VDC IN, 48VDC 802.3af OUT, 17W DCDC Converter with Gige PoE Inserter

TP-DCDC-1248GD-M

9-36VDC IN, 48VDC 802.3af OUT, 17W DCDC Converter/PoE Inserter. Metal Case

TP-DCDC-4824G

36-72VDC IN, 24VDC Passive PoE OUT, 20W DCDC Converter/ Gige PoE Inserter.

TP-DCDC-4848G

36-72VDC IN, 48VDC Passive PoE OUT, 24W DCDC Converter/ Gige PoE Inserter.

For further information contact:

Tyconsystems.com



930 W 14600 S Ste 600 Bluffdale, UT 84065
PH: 801-432-0003 FAX: 801-618-4220